

Herrmans RIMTAPES

RIMTAPES YOU CAN TRUST. Herrmans is the leading European rimpape manufacturer. In the Herrmans range you can find rimpapes suitable for all types of spoke wheels, bicycle as well as motorcycle and moped wheels, fullfilling several levels of pressure requirements.

HPM RIMTAPE (BLUE)

HPM, which is made from blue PVC, has been developed for double wall rims with a max pressure of 6 bar or 87 psi.



WIDTH	RIM DIMENSION
23mm	203/12"
20mm	305/16"
12mm	355/18"
12, 14, 16, 18, 20, 23, 27mm	406/20"
18, 20mm	451/20"
16, 23mm	451-484/20-22"
16mm	490/22"
12, 14, 16, 18, 20mm	507/24"
14, 16, 18, 20mm	540/24"
11, 12, 14, 16, 18, 20, 23, 25, 27mm	559/26"
12, 14, 16, 18, 20, 23, 25, 27mm	559-622/26-28"
11, 12, 14, 16, 18, 20, 23, 25, 27mm	622-635/28"

VALVEHOLE AVAILABLE FOR RIMS WITH AMERICAN VALVE (SHRADER VALVE) 9MM OR PRESTA VALVE 7MM.

HPS RIMTAPE (YELLOW)

HPS is made from yellow polyurethane, which makes the rimpape extremely light. This rimpape can stand a max pressure of 8 bar or 116 psi.



WIDTH	RIM DIMENSION
14, 16, 18, 20, 22, 30mm	406/20"
20, 22, 23mm	507/24"
14, 16, 18, 22mm	540/24"
10, 11, 12, 14, 16, 18, 20, 22mm	559/26"
11, 12, 14, 15, 16, 18, 20, 22, 23mm	584-590/26"
10, 11, 12, 14, 16, 18, 20, 22mm	622-635/28"

VALVEHOLE AVAILABLE FOR RIMS WITH AMERICAN VALVE (SHRADER VALVE) 9MM OR PRESTA VALVE 7MM.

HPR RIMTAPE (RED)

HPR is Herrmans latest development in the field of rimpapes. From the base of polypropylene we have developed a lightweight high performance rimpape combining the best features of HPE and HPS, strength and flexibility, max pressure of 10 bar or 145 psi. The recommended high-end choice for road racing and advanced MTB.



WIDTH	RIM DIMENSION
14, 16, 18, 20, 22, 24mm	559/26"
14, 16, 18, 20, 22, 24mm	571/650C/26"
14, 16, 18, 20, 22, 24mm	584/26"
14, 16, 18, 20, 22, 24mm	622/700C/28"

VALVEHOLE AVAILABLE FOR RIMS WITH AMERICAN VALVE (SHRADER VALVE) 9MM OR PRESTA VALVE 7MM.



ASSEMBLY RECOMMENDATIONS

